



CMR Electrical Ltd  
Bolton House  
Five Chimneys Lane  
Hadlow Down  
East Sussex  
TN22 4DX  
Tel: 01825 733600

## Oil Leak Detection Sensor for outside use Type OSPW



The sensor has been designed to detect the presence of oil or any non-conductive liquid including fuel oil, diesel etc. and energise an internal relay to provide a signal to existing alarm systems, Building Management Systems or SMS messaging systems.

The sensor as standard includes a Stainless Steel floor mounting bracket and on request can be fitted with a wall mounted bracket.

The Sensor includes two liquid detectors one looking for conductive liquids (water) with the other looking for non-conductive liquids (fuel oil etc. ) using an optical sensor. The mode of operation for the optical sensor is the principle of total internal reflection. An LED and photo-transistor are housed in a plastic (Polysulfone) dome. When no liquid is present, light from the LED is internally reflected from the dome to the photo-transistor. When a liquid covers the dome, the effective refractive index at the dome-oil boundary changes allowing some light from the LED to escape. Thus the amount of light received by the photo-transistor is reduced indicating the presence of a liquid. The conductive sensor looks for water by using bi-directional DC in both sensors to stop electrolysis of the electrodes.


Sensors can be connected together to give a common alarm within an area or connected individually to provide exact location of a leak.

**Output alarm relay truth table**


<i>Water Detected</i>	<i>Oil Leak Detected</i>	<i>Relay output Contact</i>
NO	NO	Open (no alarm)
NO	YES	Closed (alarm)
YES	NO	Open (no alarm)
Water detected first	Then an oil leak	Open (see <i>note 2</i> )
Water detected second	Oil Leak detected first	Closed (see <i>note</i> )

***Note***

If the sensor is detecting an oil leak before water is detected, the output relay will remain ON. However, if water is detected before an oil leak the relay will remain OFF until the water has evaporated when the relay will turn ON if oil is still present.



**Internal wiring**



**Specification**

Housing type  
Size excluding bracket  
Colour  
Input power  
Power Consumption  
Connections to Sensor  
Relay contact  
Ingress Protection Rating

PVCU Plastic  
75mm High x 38mm diameter  
White  
12 to 24 VAC or 12 to 24VDC  
30mA @ 24VDC  
3 metre long 4 core signal cable  
Normally Open , (close in alarm ) 1 amp 30VDC volt free contact  
IP65